

Quality Certifications:



DOT SGS



ASCENDO
INTERNASIONAL

PT. Ascendo Internasional

Jl. Palmerah Barat No.8

Kel. Grogol Utara Kec. Kebayoran Lama
Jakarta Selatan 12210. Indonesia

 021 - 5306869

    Ascendo Tbr



ASCENDO
INTERNASIONAL

AGRICULTURE TYRE



About Us

PT. Ascendo Internasional, sebuah perusahaan profesional yang berdedikasi dalam memproduksi ban berkualitas terbaik untuk produsen sepeda motor, truk, dan alat berat di seluruh dunia. Kami telah membangun reputasi yang solid atas produk-produk berkualitas tinggi kami, didukung oleh teknologi produksi terkini, dan dikelola dengan standar internasional yang ketat dalam sistem kontrol mutu. Dengan sertifikasi deperti SNI, ISO 9001:2015, European Chemical Compliance (REACH), dan lainnya, produk kami telah berhasil menembus pasar di Eropa, Amerika, dan berbagai belahan dunia.

Salah satu produk andalan kami adalah **AGRICULTURE TYRE** yang dirancang khusus untuk kendaraan agrikultural, industri, konstruksi, dan pertambangan.



TRACTOR R-1



- Civil construction, municipal works, agriculture operations, etc.
- Suitable for small tractors other machinery, with good traction and anti-skid performance.
- Applicable to conditions such as construction, municipal engineering, and agriculture.

TIRE SIZE	PR	OD (mm)	SW (mm)	RIM	LOAD CAPACITY (kg)	PRESSURE (PSI)	PATTERN	TT/TL
7.50-16 (8-16)	8	810	205	5.50F	870	54	R-1	TT
7.50-18 (8-18)	8	850	203	5.50F	670	36	R-1	TT
12.4-24	12	1160	315	W11	1750	48	R-1	TT



TRACTOR R-1



- Civil construction, municipal works, mining operations, agriculture, etc.
- Suitable for small tractors other machinery, with good traction and anti-skid performance.
- Applicable to conditions such as construction, municipal engineering, agriculture operations, and earth mining.

TIRE SIZE	PR	OD (mm)	SW (mm)	RIM	LOAD CAPACITY (kg)	PRESSURE (PSI)	PATTERN	TT/TL
13.6-24	12	1210	345	W12	2180	52	R-1	TT
14.9-24	12	1265	378	W13	2120	35	R-1	TT
18.4-30	12	1550	467	W16L	3150	33	R-1	TT
18.4-34	12	1655	467	W16L	3375	33	R-1	TT



BACKHOE R4-B



- Agricultural operations.
- The block patterns has good traction and self-cleaning performance.
- Excellent resistance to wearing and ageing performance.

TIRE SIZE	PR	OD (mm)	SW (mm)	RIM	LOAD CAPACITY (kg)	PRESSURE (PSI)	PATTERN	TT/TL
12.5/80-18	12	965	317	9	2650	54	R4 B	TL



SH216 R-1



- Civil construction, municipal works, mining operations, etc.
- Suitable for small excavators, with good traction and anti-skid performance.
- Applicable to conditions such as construction, municipal engineering, and earth mining.

TIRE SIZE	STANDARD RIM	PR	TREAD DEPTH	SW	OD	MAX. LOAD	PRESSURE	SPEED INDEX	TT/TL
			(mm)	(mm)	(mm)	(kg)	(PSI)	(km/h)	
16.9-24	W15L	12	25	430	1335	3250	38	30	TT
16.9-28	W15L	12	25	430	1435	3550	38	30	TT



SH111 R-1



- Farmland operations and short-distance transportation.
- Suitable for use on tractor drive wheels, with good traction, wear resistance, and self-cleaning performance
- Suitable for dry land operations and short distance transportation.
- Excellent resistance to weathering and ageing performance.

TIRE SIZE	STANDARD RIM	PR	TREAD DEPTH	SW	OD	MAX. LOAD	PRESSURE	SPEED INDEX	TT/TL
			(mm)	(mm)	(mm)	(kg)	(PSI)	(km/h)	
20.8-38	W18L	12	38	528	1835	3850	46	30	TT