

BIAS TYRE

Keselamatan dan Produktivitas Terjamin
dengan Ban Bias Berkualitas Tinggi



HEAD OFFICE

PT. Ascendo Internasional

Jl. Palmerah Barat No.8

Kel. Grogol Utara Kec. Kebayoran Lama

Jakarta Selatan 12210. Indonesia

 **021 - 5306869**

PRODUCT INTRODUCTION

1. Superb wear resistance and puncture resistance.
2. Suitable for all wheel position on ordinary road.



AB635



Size	PR	RIM	OD (mm)	SW (mm)	TREAD DEPTH (mm)	LOAD INDEX	Weight (kg)	Max.Load Capacity (kg)		Standard Pressure (Psi)
								Single	Dual	
10.00-20	16	7.5	1054	275	14.5	146/144K	54	3000	2800	110
11.00-20	16	8	1072	260	14.5	150/145K	54	3350	2900	110



AB111



Size	PR	RIM	OD (mm)	SW (mm)	TREAD DEPTH (mm)	LOAD INDEX	Weight (kg)	Max.Load Capacity (kg)		Standard Pressure (Psi)
								Single	Dual	
7.50-16	14	6.00G	799	157	14	122/118J	24,5	1500	1320	105
10.00-20	18	7.5	1038	198	18	150/145G	59,5	3350	2900	120



AB313



Size	PR	RIM	OD (mm)	SW (mm)	TREAD DEPTH (mm)	LOAD INDEX	Weight (kg)	Max.Load Capacity (kg)		Standard Pressure (Psi)
								Single	Dual	
7.50-16	14	6.00G	815	170	18.5	122/118J	25,5	1500	1320	105
10.00-20	18	7.5	1055	215	21	150/145G	62,5	3350	2900	120



AB316



Size	PR	RIM	OD (mm)	SW (mm)	TREAD DEPTH (mm)	LOAD INDEX	Weight (kg)	Max.Load Capacity (kg)		Standard Pressure (Psi)
								Single	Dual	
10.00-20	18	7.5	1055	198	20.5	150/145G	57	3350	2900	125



AB112



Size	PR	RIM	OD (mm)	SW (mm)	TREAD DEPTH (mm)	LOAD INDEX	Weight (kg)	Max.Load Capacity (kg)		Standard Pressure (Psi)
								Single	Dual	
11.00-20	18	8.0	1044	200	19	153/148G	55	3650	3150	125



AB535



Size	PR	RIM	OD (mm)	SW (mm)	TREAD DEPTH (mm)	LOAD INDEX	Weight (kg)	Max.Load Capacity (kg)		Standard Pressure (Psi)
								Single	Dual	
11.00-20	18	8.0	1080	221	23.5	153/148G	58	3650	3150	125